


Ra	0.2	1.6	6.3	25	Q
JIS	▽▽▽	▽▽	▽	▽	~

GENERAL TOLERANCE	±0.1 6~30 121~320 321~1000	±0.2 31~120 121~320 321~1000	±0.3 31~120 121~320 321~1000	±0.5 121~320 321~1000	±0.8 321~1000
-------------------	-------------------------------------	---------------------------------------	---------------------------------------	-----------------------------	------------------

HAITIMA CORPORATION
P.O.BOX 34-36 TAIPEI
Tel: +886-2-26585800

E-mail: haitima@seed.net.tw
R.O.C. www.haitima.com.tw
Fax: +886-2-26582266

PART D



Size	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
Size of Thread	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
G: Max O.D.	45.7	53.3	60.9	82.6	90.3	99.8	112.4	137.6	165.6	238.3
B: Overall Length	49.5	51	58.64	67.5	67	72.2	85.64	86.5	88.8	103.5
E: Exposed Length	31.4	32	39	44.5	45	50	54.3	55.5	55.5	65.5
A: Min. I.D.	18	21	25	34.9	39	50.8	63	76.2	100.8	152.6

unit:mm

△			
△			
△			
Revise	Description	Date	Approve
DRAWING NO. FK-05			
-14			



HAITIMA CORPORATION

CHECK BY

DRAWING BY

DATE

SPECIFICATION

Cam & Groove Couplers & Adapters

Sammy

Apr.21.2014

MATERIAL

SS 316

PROCESS/Nr.

UNIT / SCALE

mm

