


Ra	0.2	▽	▽	▽	▽
1.6	▽	▽	▽	▽	▽
6.3	▽	▽	▽	▽	▽
25	▽	▽	▽	▽	▽
▽	▽	▽	▽	▽	▽

±0.1	0.5~5	GENERAL TOLERANCE
±0.2	6~30	
±0.3	31~120	
±0.5	121~320	
±0.8	321~1000	

HAITIMA CORPORATION
P.O.BOX 34-36 TAIPEI
Tel:+886-2-26585800

E-mail:haitima@seed.net.tw
R.O.C. www.haitima.com.tw
Fax:+886-2-26582266

PART F



Size	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
Size of Thread	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
B: Overall Length	49	58	67.5	73.2	74.7	83.62	97	101	107.9	116.3
E: Exposed Length	34	39	48.5	52.5	54	61.7	68	70	74.6	79.2
A: Min I.D.	14.2	21	23.8	30.8	38.5	46	58	73.2	98.2	150
C: Max Across Corners of Adaptors	28.6	39.2	43.8	51.9	60.4	70.4	82.3	97.8	126.8	187.6

unit:mm



HAITIMA CORPORATION

CHECK BY

DRAWING BY

DATE

SPECIFICATION

Cam & Groove Couplers & Adaptors

Sammy

Apr.21.2014

MATERIAL

SS 316

PROCESS/Nr.

UNIT / SCALE

mm



Revise

Description

Date

Approve

DRAWING NO.

FK-06

-14